



SAFETY DATA SHEET

211USP/NFDM55M - Isopropyl Alcohol 70%

1. IDENTIFICATION OF SUBSTANCE / MIXTURE AND OF SUPPLIER

Product Identifier: High Purity Chemicals
Synonyms: Isopropanol; Isopropyl Alcohol; 2-Propanol; sec-propyl alcohol; dimethylcarbinol; sec-propanol; Rubbing alcohol; IPA 70%;
Other means of identification: CAS No. 67-63-0
EINECS No. 200-661-7

Recommended use of the chemical and restrictions on use:
General use organic solvent

Supplier Details:

CleanPro
6200 Bury Drive
Eden Prairie, MN 55346
Ph: 952.903.0333
Fx: 952.903.0315
CCN17213


Emergency Contact: CHEMTREC: 1.800.424.9300 (USA) / +1.703.527.3887 (International)

2. HAZARDS IDENTIFICATION

OSHA Hazards:
Flammable liquid, Target Organ Effect, Irritant

Target Organs:
Cardiovascular system, Gastrointestinal tract, Kidney, Liver, Nerves

NFPA



GHS label elements, including precautionary statements



Signal Word:

DANGER!

Hazard statement(s)

H225 Highly flammable liquid and vapor.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statement(s)

P261 Avoid breathing dust/fumes/gas/mist/vapors.
P312 Call a POISON CENTER or doctor/ physician if you feel unwell.
P501 Dispose of contents and container to an approved waste disposal plant.
P240 Ground/bond container and receiving equipment.
P337 + P313 If eye irritation persists: Get medical attention.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical attention.
P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P303 + P361 + P353 IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
P210 Keep away from heat, sparks, open flames, and hot surfaces. No



| | |
|-------------|--|
| P233 | smoking. |
| P102 | Keep container tightly closed. |
| P403 + P233 | Keep out of reach of children. |
| P403 + P235 | Store in a well-ventilated place. Keep container tightly closed. |
| P405 | Store in a well-ventilated place. Keep cool. |
| P243 | Store locked up. |
| P241 | Take precautionary measures against static discharge. |
| P242 | Use explosion-proof electrical, ventilating, and lighting equipment. |
| P271 | Use only non-sparking tools. |
| P264 | Use only outdoors or in a well-ventilated area. |
| P280 | Wash hands thoroughly after handling. |
| | Wear protective gloves and eye and face protection. |

GHS Classification(s)

Eye irritation (Category 2A)
 Flammable Liquids (Category 2)
 Specific target organ toxicity - single exposure (Category 3)

Other hazards which do not result in classification:**Potential Health Effects:**

| Organ | Description |
|------------|---|
| Eyes | Can cause irritation to the eyes. |
| Ingestion | Can be harmful if ingested. |
| Inhalation | Can be harmful if inhaled. Can cause respiratory tract irritation. Vapors can cause drowsiness and dizziness. |
| Skin | Can cause irritation if absorbed through skin. |

3. COMPOSITION AND INFORMATION ON INGREDIENTS

| | |
|-------------------------------|---|
| Chemical identity: | Isopropyl Alcohol 70% |
| Common name / Synonym: | Isopropanol; Isopropyl Alcohol; 2-Propanol; sec-propyl alcohol; dimethylcarbinol; sec-propanol; Rubbing alcohol; IPA 70%; |
| CAS number: | 67-63-0 |
| EINECS number: | 200-661-7 |
| ICSC number: | 0554 |
| RTECS #: | NT8050000 |
| UN #: | 1219 |
| EC #: | 603-117-00-0 |

| % Volume | Material | CAS |
|----------|-------------------|-----------|
| 68 - 72 | Isopropyl Alcohol | 67-63-0 |
| 28 - 32 | Water | 7732-18-5 |



4. FIRST AID MEASURES

General advice

Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. Consult a physician. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.

Skin

Immediately flush affected area with plenty of water while removing contaminated clothing. Wash contaminated clothing before reuse. Contact a doctor. If irritation persists, get medical attention.

Inhalation

Remove person to fresh air. If signs/symptoms continue, get medical attention. Give oxygen or artificial respiration as needed.

Eyes

Thoroughly flush the eyes with large amounts of clean low-pressure water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation persists, seek medical attention.

Ingestion

DO NOT induce vomiting. If vomiting does occur, have victim lean forward to prevent aspiration. Rinse mouth with water. Seek medical attention. Never give anything by mouth to an unconscious individual.

5. FIRE FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media:

SMALL FIRE: Use dry chemicals, CO₂, water spray or alcohol-resistant foam. LARGE FIRE: Use water spray, water fog or alcohol-resistant foam. Cool all affected containers with flooding quantities of water.

Specific hazards arising from the chemical (e.g., nature of any hazardous combustion products):

May explode when heated. Closed containers may rupture and explode during runaway polymerization. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Special protective equipment and precautions for firefighters:

Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Keep unopened containers cool by spraying with water.

Unusual Fire and Explosion Hazards:

- May produce a floating fire hazard.
- Static ignition hazard can result from handling and use.
- Vapors may travel to source of ignition and flash back.
- Vapors may settle in low or confined spaces.

Carbon oxides expected to be the primary hazardous combustion product.



Flammable Properties

Classification

OSHA/NFPA Class IB Flammable Liquid.

Flash point

18.3 °C (64.9 °F) - Closed Cup

Autoignition temperature

399 °C (750 °F) (for Isopropyl Alcohol 99%)

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Do not inhale vapors, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.

Environmental precautions:

Stop leak. Contain spill if possible and safe to do so. Prevent product from entering drains.

Methods and materials for containment and cleaning up:

Contain spill, then collect with an electrically protected vacuum cleaner or by wet-brushing and put the material into a convenient waste disposal container. Keep container closed.

7. HANDLING AND STORAGE

Precautions for safe handling:

Do not get on skin or in eyes. Do not inhale vapor or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the buildup of electrostatic charge. Open and handle container with care. Metal containers involved in the transfer of this material should be grounded and bonded.

Conditions for safe storage, including any incompatibilities:

Keep container tightly closed in a cool, dry and well ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters, e.g., occupational exposure limit values or biological limit values:

Occupational Exposure Limits

| Component | Source | Type | Value | Note |
|-------------------|------------|------|---------|------|
| Isopropyl Alcohol | US (OSHA) | STEL | 500 ppm | |
| Isopropyl Alcohol | US (ACGIH) | STEL | 400 ppm | |
| Isopropyl Alcohol | US (ACGIH) | TWA | 200 ppm | |



| | | | | |
|-------------------|-----------|-----|---------|--|
| Isopropyl Alcohol | US (OSHA) | TWA | 400 ppm | |
|-------------------|-----------|-----|---------|--|

Appropriate engineering controls:

General room or local exhaust ventilation is usually required to meet exposure limit(s). Electrical equipment should be grounded and conform to applicable electrical code.

Individual protection measures, such as personal protective equipment:

Respiratory protection:

Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection:

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Eye protection:

Use chemical safety goggles and/or a full face shield where splashing is possible. Use equipment approved by appropriate government standards, such as NIOSH (US) or EN166 (EU) Maintain eye wash fountain and quick-drench facilities in work area.

Skin and body protection:

Wear impervious, flame retardant, antistatic protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

Hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--|
| Appearance (physical state, color, etc.) | Liquid. Colorless, clear. |
| Odor | Specific data not available |
| Odor threshold | Specific data not available |
| pH | Specific data not available |
| Freezing point | -90 °C (-130 °F) (for Isopropyl Alcohol 99%) |
| Initial boiling point and boiling range | 83 °C (181°F) (for Isopropyl Alcohol 99%) |
| Flash point | 18.3°C (64.9 °F) - Closed Cup |
| Evaporation rate | Specific data not available |
| Flammability (solid, gas) | Flammable |
| Upper / Lower flammability or explosive limits | 12.7% (V) / 2% (V) (for Isopropyl Alcohol 99%) |
| Vapor pressure | 43.2 hPa (32.4 mmHg) at 20.0 °C (68.0 °F) |

| | |
|---|--|
| Vapor Density | 2.1 (for Isopropyl Alcohol 99%) |
| Relative Density | Specific data not available |
| Solubility(ies) | Miscible |
| Partition coefficient n-octanol/water(ies) | log Pow: 0.05 (for Isopropyl Alcohol 99%) |
| Auto-ignition temperature | 399 °C (750°F) (for Isopropyl Alcohol 99%) |
| Decomposition temperature | Specific data not available |
| Formula (ISOPROPYL ALCOHOL) | C3H8O |
| Formula (WATER) | H2O |
| Molecular Weight (ISOPROPYL ALCOHOL) | 60.1 g/mol |
| Molecular Weight (WATER) | 18.02 g/mol |

10. STABILITY AND REACTIVITY

| | |
|---|---|
| Chemical Stability | Avoid exposure to air any longer than necessary so as to prevent peroxide formation. Stable under recommended storage conditions. |
| Possibility of hazardous reactions | Vapors may form explosive mixture with air. |
| Conditions to avoid (e.g., static discharge, shock or vibration) | Heat, flames, and sparks. Extreme temperatures and direct sunlight. |
| Incompatible materials | Oxidizing agents, Acid anhydrides, Aluminium, Halogenated compounds, Acids |
| Hazardous decomposition products | Carbon oxides are expected to be, under fire conditions, the primary hazardous decomposition products. |

11. TOXICOLOGICAL INFORMATION

- Water 7732-18-5

Product Summary:

No data available for the teratogenic, mutagenic, or reproductive toxicity effects of this product. No data available to designate the product as causing specific target organ toxicity through single or repeated exposure. No data available to designate product as an aspiration hazard or as a respiratory or skin sensitizer.

Acute Toxicity:

| | | | |
|-------------------|-----------|-------------|-----------------|
| No data available | Oral LD50 | Dermal LD50 | Inhalation LC50 |
|-------------------|-----------|-------------|-----------------|

Irritation:

Eyes

No data available.

Skin

No data available

Carcinogenicity



IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Other Hazards

| Organ | Description |
|------------|---|
| Eyes | No known hazards. |
| Ingestion | No known hazards. |
| Inhalation | Can be harmful if inhaled. Can cause irritation to upper respiratory tract. |
| Skin | No known hazards. |

- Isopropyl Alcohol 67-63-0

Product Summary:

Long-term exposure (2 years) to Isopropyl Alcohol via inhalation at concentrations up to 5000 ppm caused no exposure related increases in tumors in animals. No data available for the teratogenicity, mutagenicity, or reproductive toxicity of this product. No data available to designate the product as causing specific target organ toxicity through repeated exposure. No data available to designate product as an aspiration hazard.

Acute Toxicity:

| | | | |
|-----------------|--------|--------------|--|
| LC50 Inhalation | Rat | 16,000 mg/kg | 8 hours |
| LD50 Dermal | Rabbit | 12,800 mg/kg | |
| LD50 Oral | Rat | 5045 mg/kg | Behavioral abnormalities observed such as altered sleep time and decreased activity. |

Irritation:

Eyes

Rabbit - Irritating to eyes - 24 hours

Eyes (ISOPROPANOL)

Mildly irritating to the eye at an airborne concentration of 400 ppm, unpleasant at 800 ppm.

Respiratory or Skin Sensitization

No data available

Skin



Rabbit- mild skin irritation

Specific target organ toxicity - single exposure (Globally Harmonized System)

Inhalation - May cause drowsiness or dizziness. - Central Nervous System

Carcinogenicity

IARC: Group 3: Not classifiable as to its carcinogenicity to humans.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Other Hazards

| Organ | Description |
|------------|--|
| Eyes | Produces irritation, characterized by a burning sensation, redness, tearing, inflammation, and possible corneal injury. May cause transient corneal injury |
| Ingestion | Causes gastrointestinal irritation with nausea, vomiting and diarrhea. May cause kidney damage. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. |
| Inhalation | Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. May cause narcotic effects in high concentration. Causes upper respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal. The probable oral lethal dose in humans is 240 ml (2696 mg/kg), but ingestion of only 20 ml (224 mg/kg) has caused poisoning. |
| Skin | May cause irritation with pain and stinging, especially if the skin is abraded. Isopropanol has a low potential to cause allergic skin reactions; however, rare cases of allergic contact dermatitis have been reported. May be absorbed through intact skin. Dermal absorption has been considered toxicologically insignificant. |
| Chronic | Prolonged exposure can be irritating to mucous membranes, skin, and the respiratory system. Can cause liver and kidney damage. |

12. ECOLOGICAL INFORMATION

- Water 7732-18-5

Ecotoxicity (aquatic and terrestrial, where available):

Ecotoxicity

Not Applicable

Persistence and degradability:

No data available

Bioaccumulative potential:

No data available

Other adverse effects:

No data available

- Isopropyl Alcohol 67-63-0
-

Ecotoxicity (aquatic and terrestrial, where available):

Acute Fish Toxicity (ISOPROPANOL)

LC50 / 96 hours Pimephales promelas: 9,640 mg/L

Toxic to Daphnia and Other Aquatic Invertebrates

EC50 / 24 h / Water Flea - 5,102 mg/L

Toxicity to Aquatic Plants (ISOPROPANOL)

EC50 / 72 hours Desmodemus subspicatus > 2,000 mg/L

Toxicity to Daphnia and other aquatic invertibrates

Immobilization EC50 / 24h / Water flea - 6,851 mg/L

Persistence and degradability:

No data available

Bioaccumulative potential:

No data available

Other adverse effects:

No data available

13. DISPOSAL CONSIDERATIONS

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:

Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this



material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

14. TRANSPORT INFORMATION

Description of waste residues and information on their safe handling and methods of disposal:

| | |
|-------------------------------|-------------|
| UN number | 1219 |
| UN proper shipping name | Isopropanol |
| Transport hazard class(es) | 3 |
| Packing group (if applicable) | II |

IMDG

UN-Number: 1219 Class: 3 Packing Group: II

EMS-No: F-E, S-D

Proper shipping name: ISOPROPANOL

Marine pollutant: No

IATA

UN-Number: 1219 Class: 3 Packing Group: II

Proper shipping name: Isopropanol

15. REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product in question:

OSHA Hazards

Flammable liquid, Target Organ Effect, Irritant

All ingredients are on the following inventories or are exempted from listing

| Country | Notification |
|--------------------------|--------------|
| Australia | AICS |
| Canada | DSL |
| China | IECS |
| European Union | EINECS |
| Japan | ENCS/ISHL |
| Korea | ECL |
| New Zealand | NZIoC |
| Philippines | PICCS |
| United States of America | TSCA |

SARA 302 Components

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 Components

The following components are subject to reporting levels established by SARA title III, Section 313: ISOPROPYL



ALCOHOL (CAS# 67-63-0) Revision date: 1987-01-01.

SARA 311/312 Hazards

Acute Health Hazard
Chronic Health Hazard
Fire Hazard

CERCLA

No chemicals in this material with known CAS numbers are subject to the reporting requirements of CERCLA

Massachusetts Right To Know Components

Isopropyl Alcohol CAS-No. 67-63-0 Revision Date 1987-01-01

Pennsylvania Right To Know Components

Isopropyl Alcohol CAS-No. 67-63-0 Revision Date 1987-01-01

Water CAS-No. 7732-18-5

New Jersey Right To Know Components

Isopropyl Alcohol CAS-No. 67-63-0 Revision Date 1987-01-01

Water CAS-No. 7732-18-5

California Prop 65 Components

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**16. OTHER INFORMATION:
INCLUDING INFORMATION ON PREPARATION AND REVISION OF THE SDS**

Disclaimer

CleanPro believes that the information on this MSDS was obtained from reliable sources. However, the information is provided without any warranty, expressed or implied, regarding its correctness. Some information presented and conclusions drawn herein are from sources other than direct test data on the substance itself. The conditions or methods of handling, storage, use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, CleanPro does not assume responsibility and expressly disclaims liability for loss, damage, or expense arising out of or in any way connected with handling,



storage, use, or disposal of this product. If the product is used as a component in another product, this MSDS information may not be applicable. Information is correct to the best of our knowledge at the date of the MSDS publication.