

SHOWA

**386**

Gray

Microporous nitrile coating over engineered DURACoil liner reinforced with HPPE.

### [ FEATURES

- Multifilament polyester wrapping DURACoil liner reinforced with HPPE
- EN 388:2016 Cut Level C
- ANSI/ISEA 105-16: A3
- Microporous nitrile coated palm for good grip & aeration
- Excellent fitting due to optimal liner design
- Unique SHOWA ergonomic shape that replicates the natural curve of the human hand I
- Seamless knit
- High abrasion resistance level 4

### [ BENEFITS

- Increased cut resistance performance due to engineered DURACoil wrapping technology
- Microporous nitrile coating protects the hand from oils and abrasions while remaining breathable
- Maximum comfort when performing delicate tasks due to soft and flexible HPPE properties combined with high multifilament wrapping technique
- High level of flexibility and dexterity due to advanced grip technology
- Ergonomically designed to replicates the natural curves for enhanced dexterity and longer use
- Embossed nitrile palm finish disperses oil away to increase grip and longevity in light oily environments.
- Cost-efficient gloves that can be laundered and re-used.

### [ INDUSTRY



Automotive



Construction



Engineering



Manufacturing



Mechanical

### [ IDEAL APPLICATIONS

- Intricate parts handling
- Brick laying
- Flashings and seals
- Maintenance
- Steel fixing
- Component Assembly



### MATERIAL

- Engineered yarn
- HPPE
- Polyester

### COATING

- Microporous nitrile

### STANDARDS



ANSI / ISEA  
105-2016



CUT

SHOWA

**386**

Gray



**PACKAGING**

- 12 Pair per polybag
- 6 Polybags per case
- 72 Pair per case



**COLOUR**

- Gray



**SIZES**

- S
- M
- L
- XL
- XXL



**[ YOU MIGHT ALSO BE INTERESTED IN**

SHOWA  
**546**



**MATERIAL**  
Engineered yarn  
**COATING**  
Polyurethane

SHOWA  
**576**



**MATERIAL**  
Engineered yarn  
**COATING**  
Foam nitrile

SHOWA  
**346**



**MATERIAL**  
Engineered yarn  
**COATING**  
Latex

SHOWA  
**577**



**MATERIAL**  
Engineered yarn  
**COATING**  
Foam nitrile

**[ USER INSTRUCTIONS**

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

**[ DISCLAIMER**

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

**Get in touch**

SHOWA USA | 579 Edison Street - Menlo, GA 30731, USA

USA@SHOWAGroup.com

© SHOWA Group 2018 | All rights reserved