

SHOWA

**4568**

Yellow

Engineered to endure, SHOWA 4568 combines DuPont™ Kevlar® cut-resistance with Zorb-IT® oil grip to deliver cut, abrasion and flame resistance, without sacrificing comfort or grip. Utilizing SHOWA's renowned ergonomic design, 4568 naturally contours to your hand for maximum precision and dexterity.


**[ FEATURES**

- 15-gauge engineered liner made with Kevlar®
- Lightweight, seamless knit
- ANSI Cut Resistance Level A4
- Sponge nitrile palm finish
- Ergonomic design

**[ BENEFITS**

- High cut and abrasion resistance
- Kevlar(R) liner is inherently flame resistant
- Lightweight, breathable liner allows warm air and moisture from inside to escape, keeping your hands dry and comfortable.
- Zorb-IT foam nitrile palm finish absorbs oil to increase grip and durability in oily environments.
- Ergonomically designed to replicate the hands's natural curves for easy movement and comfortable, continuous wear.
- Seamless knit liner increases dexterity

**[ INDUSTRY**

-  **Aerospace**
-  **Automotive**
-  **Construction**
-  **Glass**
-  **Oil and Gas**

**[ IDEAL APPLICATIONS**

- Mechanical and engineering
- Light assembly of oil-coated pieces
- Steel fixing
- Handling glass and windows
- Deck crew



**TAA PRODUCTS**

**MADE IN USA**

**MATERIAL**

- Kevlar

**COATING**

- Nitrile

**GRIP**

- Foam

**STANDARDS**



SHOWA

**4568**

**Yellow**



**PACKAGING**

- 12 Pair per polybag
- 6 Polybags per case
- 72 Pair per case



**COLOUR**

- Yellow



**SIZES**

- S
- M
- L
- XL
- XXL



**[ YOU MIGHT ALSO BE INTERESTED IN**

SHOWA  
**4561**



**MATERIAL**  
Kevlar  
**COATING**  
Foam nitrile

SHOWA  
**S-TEX 581**



**MATERIAL**  
Kevlar  
**COATING**  
Foam nitrile

SHOWA  
**257**



**MATERIAL**  
Aramid knit  
**COATING**  
Foam nitrile

SHOWA  
**250**



**MATERIAL**  
Kevlar  
**COATING**  
Foam nitrile

**[ USER INSTRUCTIONS**

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

**[ DISCLAIMER**

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

**Get in touch**

SHOWA USA | 579 Edison Street - Menlo, GA 30731, USA

USA@SHOWAGroup.com

© SHOWA Group 2018 | All rights reserved