

# VT 60 Wet/Dry Vacuums

- electric or pneumatic variations to meet industry requirements

The combination of efficient design and powerful suction allows the Nilfisk VT 60 Wet/Dry vacuums to simultaneously pick up wet and dry debris without special adapters or filter switching. Featuring a unique four-stage filtration system and multiple collection and disposal options, the versatility of these vacuums is ideal for multiple wet/dry applications.

While the standard VT 60 is an electric version, the VT 60A is air-operated for environments where electricity is not available or is undesirable, and the VT 60CR is designed specifically for cleanroom applications.

## Features and Benefits

- Multi-stage filtration system designed for liquid or dry pick-up, with no filter change or adjustment
- Detachable trolley features sturdy polyethylene construction and large, smooth wheels for easy decontamination and added maneuverability
- Foam impact filter fits over and protects the float valve from clogging debris
- Pliable rubber inlet tube designed to relieve caking and clogging caused by collection of damp or sticky material
- Multiple accessories are available for a wide variety of applications



## Technical Specifications

Description	Unit	VT 60	VT 60A	VT 60CR
Collection Type	-	Wet/Dry	Wet/Dry	Wet/Dry
Type of Power	-	1-Phase	1-Phase	1-Phase
Voltage @ 60 Hz	V	120	-	120
Power @ 60 Hz	HP (W)	1.34 (1000)	-	1.34 (1000)
Waterlift, max.	in. (mm) H <sub>2</sub> O	117 (2972)	172 (4369)	117 (2972)
Airflow, max.	CFM (L/min)	99 (2803)	140 (3964)	99 (2803)
Current, max.	amps	8.3	-	8.3
Container Capacity	gal. (L)	15 (56.8)	15 (56.8)	15 (56.8)
Orifice Diameter, hose	mm	38	38	38
Dimensions (L x W x H)	in. x in. x in. (mm x mm x mm)	24.0 x 21.5 x 37.5 (610 x 546 x 953)	24.0 x 21.5 x 37.5 (610 x 546 x 953)	24.0 x 21.5 x 37.5 (610 x 546 x 953)
Weight	lbs. (kg)	65 (29)	60 (27)	65 (29)
Cord Length	ft. (m)	30 (9)	30 (9)	30 (9)
Sound Pressure Level @ 3'3" (ISO 3744)	dB(A)	75	77	75

*Specifications and details are subject to change without prior notice.*