



www.wearwell.com

## Endurable Anti Fatigue Mats

### Group 459

Endurable outlasts lower quality blown sponge products. The technical reason is its “dual layer” construction. The practical result is that a thicker, denser PVC surface withstands abrasion and foot traffic while the softer under layer provides ergonomic relief. Endurable is a great value for the investment.

- Economic relief for medium traffic areas
- Safety beveled edges
- Overall thickness 1/2” (13 mm)

<b>Type</b>	Anti-Fatigue Matting
<b>Suitable Environment</b>	Dry
<b>Customization Level</b>	C1 - Custom Length
<b>Solid or Drainage</b>	Solid
<b>Compound</b>	Dual Density PVC Sponge
<b>Recycled</b>	<10%
<b>Warranty</b>	1 Year

Property	Test / Result
Flammability	MVSS 302 / 'A'; Rating
Taber Abrasion	Fed Std. 191 / 2% lost @ 1,000 cycles
Temperature Range	Not Available
Coefficient of Friction	ASTM F1677 / Dry: COF = .91
Compression Deflection	ASTM D575 / .23 inches @ 35 psi
Tear Strength	Not Available
ESD Rating	Not Available
Dielectric Strength	Not Available

SKU	UPC	Color	Thickness	Dimensions	Stock Part	UOM
459.12x2x3BK	715411252138	Black	0.5	2' x 3'	Y	EA
459.12x2x60BK	715411252077	Black	0.5	2' x 60'	Y	RL
459.12x3x12BK	715411252312	Black	0.5	3' x 12'	Y	EA
459.12x3x5BK	715411252374	Black	0.5	3' x 5'	Y	EA
459.12x3x60BK	715411252251	Black	0.5	3' x 60'	Y	RL
459.12x4x60BK	715411252497	Black	0.5	4' x 60'	Y	RL