



BULLHEAD SAFETY® HEARING PROTECTION

Uncorded Polyurethane Foam NRR 33 dB Earplugs

DESCRIPTION

These single-use foam earplugs provide simple, effective protection against hearing damage by greatly reducing environmental noise. Highly visible orange and shaped to conform to the ear canal, the soft, slow-recovery foam is rated for a protection level of NRR 33 dB.

Each pair is individually packaged in a polybag for retail sale.



INDUSTRY	
Airport Crews	Utility Work
Construction	Transportation
Automotive	Manufacturing
Printing	Waste Management

FEATURES

- Single-use disposable earplugs
- 100% PVC-free polyurethane foam
- Extra-soft, lightweight foam seals the ear canal without pressure
- Bullet shaped provides a snug fit while gently conforming to the ear canal
- Expandable, slow rebound foam provides the best combination of comfort and protection for most users
- Made of soft non-allergenic material

ITEM **HP-F1**

NRR **33 DB**



SPECIFICATIONS

MATERIAL	COLOR	SHAPE	CORDED	METAL DETECTABLE	POLY BAGGED	RETAIL READY	PAIRS/BOX
PVC-Free Polyurathane Foam	High-Visibility Orange	Bullet	No	No	Individual Pairs	Yes	200
EN 352-2: 2002 SNR RATING	ANSI S3. 19-1974 NRR RATING						
36 dB	33 dB						

ANSI S3.19-1974 SOUND ATTENUATION DATA:

FREQUENCY (HZ)	125	250	500	1000	2000	3150	4000	6300	8000	NRR
MEAN ATTENUATION (DB)	28.7	25.9	31.3	27.3	35.1	39.4	40.3	46.2	46.2	33 dB
STANDARD DEVIATION (DB)	5.5	4.5	4.5	2.8	4.3	4.2	5.6	6.1	3.7	

EN 352-2: 2002 SOUND ATTENUATION DATA:

FREQUENCY (HZ)	63	125	250	500	1000	2000	4000	8000
SOUND ATTENUATION (DB)	18.8	15.4	17.9	27.8	36.3	35.4	42.4	39.5
STANDARD DEVIATION (DB)	4.1	4.1	3.5	2.7	3.7	3.6	2.6	5.4
ASSUMED PROTECTION (DB)	14.7	11.3	14.4	25.1	32.6	31.8	39.8	34.1
	SNR = 36 dB	H = 34 dB	M = 34 dB	L = 31 dB				

PACKAGING

	QUANTITY	HP-F1
EACH PAIR	1	810292029616
INNER BOX	200 PAIRS/PACK	10810292029507
CASE	10 PK/CASE	20810292029504
CASE WEIGHT (IN POUNDS)		11.5

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
sales@BullheadSafety.com

BullheadSafety.com

