

STAT PRO 3D PRINTING FILAMENT DRY CABINET MODEL NO. ADL-3D77



Specifications of ADL-3D77



Digital hygrometer

Automatic Electronic
Drying Unit



RH Range	≤10%RH±5%RH, FRT<2HRS
External Dimensions	W40.0 x H 55.5 x D 44.5 cm W15.75x H 21.85 x D 17.5 inch
Internal Dimensions	W32.0 x H 46.0 x D 32.5 cm W12.6x H 18.1 x D 12.8 inch
Capacity	79L Up to 16 x 1kg 200mm spools (estimated)
Door	PVC Frame with Glass Door
Cabinet	High Quality Steel Airtight Cabinet
	Anti-rust Coating
Shelves	1 Adjustable Hanging Rod & 4 Filament Feed Ports for Direct Printing
Power Consumption	12W (avg.)
Voltage	110V/0.9A (220V are available upon request)
Hygrometer	Digital hygrometer Accuracy : ±3%RH (0~80%RH), ±0.3°C (20~40°C)

Instrument name:					
Start time: 7/17/2020 4:41:57 PM		Minimum	Maximum	Mean value	Limit values
End time: 7/20/2020 11:02:57 AM	Humidity [%RH]	4.8	58.0	7.589	0.0/100.0

