

### Description

PTFE Glass Cloth tapes are constructed using PTFE impregnated glass cloth with silicone adhesive. CGS 6157 also has a yellow paper liner option.

### Product Applications

Used in many application which is requiring high temperature performance and high abrasion resistance. Easy release surface on packaging and heat sealing machines, ironing and pressing equipment.

### RoHs/REACH Compliant

This product complies with the European Union's "Restriction of Hazardous Substances" (RoHs) initiative and with European REACH regulation.

### Product Construction

- PTFE Glass Cloth Backing
- Silicone Adhesive
- Brown

### Nominal Values

The following data are nominal values based on PSTC, ASTM and other standard tests. The data should not be considered as specifications.

Specification				Test Methods
<b>Backing Thickness</b>	3 mil	5 mil	10 mil	ASTM D-3652
<b>Total Thickness</b>	5 mil	7 mil	12 mil	ASTM D-3652
<b>Adhesion to Steel</b>	30 oz./in	30 oz./in	30 oz./in	ASTM D-3330
<b>Tensile Strength</b>	100 lbs./in	180 lbs./in	225 lbs./in	ASTM D-3759
<b>Elongation</b>	5%	5%	5%	ASTM D-3759
<b>Dielectric Strength</b>	2400V	3000V	6300V	ASTM D-149
<b>Operating Temperature Range</b>	-100°F to 500°F	-73°C to 200°C	-100°F to 500°F	

