

A Series (Transformerless Type) Model DLV30A/45A-SPC For Machine Screws #3 - #13 (2.6 - 6.0 mm)

Features

Eco-friendly electric screwdrivers with built-in brushless motors to use with a screw fastening counter

- Extensive torque range from 3.5 to 39.8 Lb-in
- Available models with speeds of 650, 1200 or 2000 rpm
- Lever Start and Push to Start type models are available
- Includes a torque adjustment ring cover
- Design conforms to the RoHS Directive for the environmentally conscious user
- Includes an easily detachable Pistol Grip DLW2300 (TD00335) as a standard accessory (DLV45A)



DLR5040A



DLR5340



DLV30A06P



DLV30A12L



DLV30A20P



DLV45A12L

Specifications

Electric Screwdriver										
Model	Starting Method	Free Speed rpm	Torque Adjustment Lb-in(Nm)		Screw Size (for reference)		Weight lbs(g)	Bit	Input Voltage	Power Consumption
			Low Torque Spring*1 (Standard Accessory)	High Torque Spring*2 (installed)	inch thread	metric coarse thread				
DLV30A06L-SPC (ADK)	Lever Start	650	3.5 - 14.2 (0.4 - 1.6)	10.6 - 26.6 (1.2 - 3.0)	#3 - #11	2.6 - 5.0 mm	1.54 (700)	Hex 1/4"	115 V AC, 50/60 Hz	55 W
DLV30A12L-SPC (ADK)		1200								
DLV30A20L-SPC (ADK)		2000								
DLV30A06P-SPC (ADK)	Push to Start	650								
DLV30A12P-SPC (ADK)		1200								
DLV30A20P-SPC (ADK)		2000								
DLV45A06L-SPC (ADK)	Lever Start	650	17.7 - 39.8 (2.0 - 4.5)	#9 - #13	4.5 - 6.0 mm	1.92 (870) with Pistol Grip				
DLV45A12L-SPC (ADK)		1200								
DLV45A06P-SPC (ADK)	Push to Start	650								
DLV45A12P-SPC (ADK)		1200								

Controller DLR5040A-WU,DLR5340-WU (see page 11)

Screw Counter for SPC (ADK)

Model	Count	Input Voltage	External Dimensions	Weight lbs(g)	Standard accessories
DLR5040A-WU	1 - 99	100 - 240 V AC, 50/60 Hz	W101 x H60 x D130 mm	1.21 (550)	80" (2 m) cord with UL three-prong plug
DLR5340-WU	0 - 99		W150 x H60 x D120 mm	1.76 (800)	

*1: Standard Accessory, *2: Built-in.

The voltage of the dedicated screwdrivers for DLR5040A/5340-WU is 115 V.

Standard Accessories

For DLV30A	<ul style="list-style-type: none"> • Bit NK35 x 2 x 7 x 75 • Suspension Bail • Low Torque Spring
For DLV45A	<ul style="list-style-type: none"> • Bit NK35 x 2 x 7 x 75 • Suspension Bail • Pistol Grip (DLW2300)

Optional Accessories



Torque Diagram (for reference)

