



24/SEVEN® LockSafe® MAX Diamond-Plate-GR

Group 583-GR

[24/SEVEN® LockSafe® MAX](#) combines the benefits of a modular product with all the comfort of an anti-fatigue mat. Each 3 ft x 3 ft (91cm x 91cm) tile features secure, seamless connections on all sides. The resilient, long-lasting Nitricell sponge base makes 24/SEVEN® LockSafe® MAX the ultimate solution for prolonged standing in areas big and small.

The male and female connectors feature a flange that **lock together and won't come apart until you want them to**. Traditional modular rubber mats have passive connections that fail, leaving dangerous, unsightly trip hazards. 24/Seven MAX saves the time and labor of continual assembly and potential workers' comp claims.

Choose 24/SEVEN® LockSafe® MAX for a dependable, safe, ergonomic floor.

- Diamond-Plate surface pattern
- Large 3 ft x 3 ft tiles (91cm x 91cm)
- Grease Resistant Rubber
- Also available with a [smooth, lightly texture](#) surface
- U.S. PATENT No. D882,293 S

| | |
|-----------------------------|---|
| Type | Anti-Fatigue Flooring |
| Suitable Environment | Dry |
| Customization Level | C3 - Full Custom (Length, Width, Shape) |
| Solid or Drainage | Solid |
| Compound | GR/Natural Rubber |
| Recycled | 25% |
| Warranty | 1 Year |

| Property | Test / Result |
|-------------------------|---|
| Flammability | MVSS 302 / 'A'; Rating |
| Taber Abrasion | Federal Standard 191 Modified / 1% loss |
| Temperature Range | 10 to 140 F |
| Coefficient of Friction | ASTM F1677 / Dry: COF = .84 / Wet COF = .45 |
| Compression Deflection | Not Applicable |
| Tear Strength | Not Applicable |
| ESD Rating | Not Applicable |
| Dielectric Strength | Not Applicable |

| SKU | UPC | Color | Thickness | Dimensions | Stock Part | UOM |
|---------------|--------------|-------|-----------|------------|------------|-----|
| 583.1x3x3GRBK | 715411014392 | Black | 1 | 3' x 3' | Y | EA |