# **Safety Data Sheet**



Revision Number: 001.0 Issue date: 06/22/2022

## 1. PRODUCT AND COMPANY IDENTIFICATION

**IDH** number:

Product name: LOCTITE 408 INSTANT ADHESIVE

known as 408 Prism® Instant

Adhesive Lo

**Product type/use:** AdhesiveCyanoacrylate

Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Item number: 40861
Region: United States

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

233742

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

#### 2. HAZARDS IDENTIFICATION

WARNING: BONDS SKIN IN SECONDS.

COMBUSTIBLE LIQUID. CAUSES EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
EYE IRRITATION	2B

PICTOGRAM(S)	
None	

#### **Precautionary Statements**

Prevention:

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Wash affected area

thoroughly after handling. Wear protective gloves, eye protection, and face protection.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. In case of fire:

Use foam, dry chemical or carbon dioxide to extinguish.

Storage:

IDH number: 233742

Store in a well-ventilated place. Keep cool.

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Beta-Methoxyethyl Cyanoacrylate	27816-23-5	80 - 100

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If symptoms persist, seek medical advice. If not breathing,

give artificial respiration. If breathing is difficult, oxygen should be

administered by qualified personnel.

Skin contact: Rinse with running water and soap. Do not pull bonded skin apart. It may be

gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water. If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action. If symptoms develop and persist, get medical

attention.

**Eye contact:** Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Seek medical attention immediately. Do not force eye open. Medical advice should be sought in case solid particles of cyanoacrylate trapped

behind the eyelid cause any abrasive damage.

Ingestion: Seek immediate medical attention. Do not induce vomiting. Never give

anything by mouth to an unconscious person. Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separated

mass.

Symptoms: See Section 11.

Notes to physician: Surgery is not necessary to separate accidentally bonded tissues. Experience

has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they should be treated

symptomatically after adhesive is removed.

#### 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Use extinguishing measures appropriate to local circumstances and the

surrounding environment. Water spray (fog), foam, dry chemical or carbon

dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear. Keep unnecessary personnel away. In case of fire, keep

containers cool with water spray.

Unusual fire or explosion hazards: None

Hazardous combustion products: Toxic fumes. Irritating vapors. Oxides of carbon.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not allow product to enter sewer or waterways. Prevent further leakage or

spillage if safe to do so.

Clean-up methods: Ensure adequate ventilation. Wear appropriate personal protective equipment.

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Cured material can be disposed of as non-hazardous waste.

## 7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed. See Section 8 of the SDS for Personal Protective Equipment. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns. When using, do not eat,

drink or smoke.

Storage: Not available.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## **EXPOSURE CONTROLS / PERSONAL PROTECTION**

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Beta-Methoxyethyl Cyanoacrylate	None	None	None	0.2 ppm TWA

**Engineering controls:** Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Wear safety glasses with side shields. Full face protection should be used if

the potential for splashing or spraying of product exists.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact. Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon or cotton. The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the

relevant EN standard.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Colorless to yellow

Odorless Odor: Odor threshold: Not available. Not applicable :Ha

Vapor pressure: < 0.2 mm hg < 0.3 mbar None < 30.0000000 Pa None < 700 mbar (50 °C

(122°F)) no method

> 149 °C (> 300.2 °F)None Boiling point/range:

Melting point/ range: Not available. Vapor density: Not available. Flash point: 80 °C (176°F) Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable Evaporation rate: Not available.

Solubility in water: Polymerises in presence of water.

Partition coefficient (n-octanol/water): Not available.

VOC content: < 2 %; < 20 g/l California SCAQMD Method 316B

4.0 - 8.0 mPa.s Viscosity: **Decomposition temperature:** Not available.

IDH number: 233742

## 10. STABILITY AND REACTIVITY

**Stability**: Stable under recommended storage conditions.

Hazardous reactions: Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and

alcohols.

Hazardous decomposition

products:

Oxides of carbon. None if used for intended purpose.

Incompatible materials: Water. Alcohols. Amines. Bases.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials. Protect from direct sunlight.

Store away from incompatible materials.

# 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### Potential Health Effects/Symptoms

Inhalation: May cause respiratory tract irritation. Exposure to vapors above the established exposure limit

results in respiratory irritation, which may lead to difficulty in breathing and tightness in the

chest.

Skin contact: Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause

allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the

skin. Cured adhesive does not present a health hazard even if bonded to the skin.

**Eye contact:** Irritating to eyes. Causes excessive tearing. Eyelids may bond.

Ingestion: Not expected under normal conditions of use. Not expected to be harmful by ingestion. Rapidly

polymerizes (solidifies) and bonds in mouth. It is almost impossible to swallow.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
Beta-Methoxyethyl Cyanoacrylate	None	Irritant, Allergen	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Tiazar acae compensin(e)	ivii Garomogon	nate caromogen	(Specifically Regulated)
Beta-Methoxyethyl Cyanoacrylate	No	No	No

# 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Recommended method of disposal: Not available.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Combustible liquid, n.o.s. (Cyanoacrylate ester)

Hazard class or division: Combustible Liquid

Identification number: NA 1993 Packing group: III

# International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

IDH number: 233742 Product name: LOCTITE 408 INSTANT ADHESIVE known as 408 Prism® Instant Adhesive Lo

Page 4 of 5

#### Water Transportation (IMO/IMDG)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

#### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Reactive, Fire, Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Beta-Methoxyethyl Cyanoacrylate (CAS# 27816-23-5).

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

**Canada Regulatory Information** 

IDH number: 233742

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

#### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Product Safety and Regulatory Affairs

**Issue date:** 06/22/2022

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.