



WT 1010M 1 CHANNEL MICRO SOLDERING KIT, 95 W, 120 V

ORDER NO: WT1010M

COMPACT. POWERFUL. VERSATILE.
BOOST YOUR PRODUCTIVITY

Discover the WT 1M Soldering Station, your ultimate productivity partner.

With extremely fast heat-up and recovery times, it handles all tasks effortlessly. No more juggling tools or compromising performance – just reliable versatility and unmatched value. Choose worry-free precision and unstoppable productivity. Choose Weller WT Soldering Stations.

+ KEY FEATURES

- > **1 CHANNEL MICRO SOLDERING KIT (95 W)**
to cover micro and standard soldering tasks including
WTMP MS Micro pencil with active (cartridge) tip technology
- > **RTM TIP FAMILY**
with 5 seconds heat-up time
- > **HIGH PRODUCTIVITY**
- > **INTUITIVE USE**
thanks to clear menu structure
- > **REDUCED FOOTPRINT**
thanks to stackability
- > **GRAPHICAL BACKLIT LC-DISPLAY**
- > **HIGH PERFORMANCE AND FUNCTIONALITY**
many connectable tools
- > **HOUSING COVER**
useable as storage
- > **OFF TIME, PROCESS WINDOW,**
Lock function, Offset
- > **STACKABLE UNITS**
useable as storage
- > **CONNECTABLE TO**
ZeroSmog Fume Extraction Units
- > **ESD-SAFE** 

SCOPE OF SUPPLY

WT1M Power Unit, 120V
 WTMP MS Soldering Iron, 12V
 RTM 013 S MS Micro Soldering Tip
 WSR 205 Safety Rest with Stop & Go Function

TECHNICAL DATA SOLDERING STATION WT 1010M

Dimensions L x W x H (mm) 150 x 130 x 101
 Dimensions L x W x H (inch) 5.91 x 5.12 x 3.98

Fuse 120V (mA) T1

Weight approx. (kg) 1,9

Mains supply voltage (V/Hz)
120 / 50

Power consumption (W) 95

Safety class I, antistatic housing
III, Soldering tool

Temperature range / Tool dependent
°C 50 - 450 / 550

Temperature accuracy °C ± 9 / ± 17

Temperature stability °C ± 2

Subject to technical alterations and amendments.

TECHNICAL DATA SOLDERING IRON WTMP MS

Temperature range °C 100 - 450
 Temperature range °F 150 - 950

Power consumption (W) 40W (55W)

Mains supply voltage (V/Hz) 12V / AC

Heat-up time (50°C to 350°C) (120°F to 660°F) 5 sec.

Safety rest WSR 205

Tip type series RTM MS

Supply unit WT 1M, WT 2M, WR 3M

Subject to technical alterations and amendments.